



Cu/PVC
450/750V
H07V2-U

DESCRIPTION:

450/750V for H07V2-U, 90° C

CABLE STRUCTURE:

Conductor:

Bare solid copper

Insulation:

PVC

TECHNICAL DATA:

Voltage Rating (U_o/U)

450/750V

Temperature Rating

-30°C to +90°C

Minimum Bending Radius

4 x overall diameter

APPLICATION:

This cable is equipped with 90°C PVC insulation and a solid conductor, and is suitable for fixed installation. It can be installed in conduit or duct systems, or used as a connection wire in switch cabinets and similar applications.

CERTIFICATES:

We hold SAA, CE, TUV and CCC certifications for our product categories. Additionally, we possess other authoritative certifications recognized in various countries and regions. For further details on our certification portfolio, please do not hesitate to contact us.

STANDARD:

Construction EN 50525-2-31

Conductor IEC 60228.1

Flame retardant EN 50575:2014 + A1:2016

Flame retardant IEC 60332-1-2





Cu/PVC 450/750V H07V2-U

Specifications

Type Code	Cross-section	Nominal Outer Diameter	Current rating, installation in open air, ambient 30° C	Total weight
	[mm]	[mm]	[A]	[kg/km]
H07V2-U	1,5	2,8	24	20
H07V2-U	2,5	3,4	32	31
H07V2-U	4	3,8	42	46
H07V2-U	6	4,3	54	68
H07V2-U	10	5,4	73	111