



MYJV 8.7/10 kV Coal Mine Used XLPE Insulated PVC Sheathed Power Cable

CABLE STRUCTURE:

Conductor:

Copper

Insulation:

XLPE

Shielding layer:

Copper tape shielding

Sheath:

PVC

SPECIFICATION RANGE:

Wire Core:

25 - 300 mm²

STANDARD:

MT 818.13-2009

APPLICATION:

Suitable for fixed installation in power distribution networks with rated voltage of 10 kV or less, or in industrial installations.

CERTIFICATES:

Our series of mining products have undergone strict review by the National Coal Mine Safety Supervision Bureau and have obtained the Coal Mine Safety Mark Certification (MA Certification), providing a reliable guarantee for coal mine safety production.

TECHNICAL DATA:

Rated voltage:(U₀/U)

8.7/10 kV

Temperature classification:

The cable conductor is permitted to have a maximum long-term operating temperature not exceeding 90°C. During a short circuit (with the maximum duration not exceeding 5 seconds), the maximum temperature of the cable conductor does not exceed 250°C.

When laying the cables on the ground, the ambient temperature during the laying process should not be lower than 0°C.

Min.Bending Radius:

3 core : 15(D+d)±5%

Finished product voltage test:

Wire core: 30.5kV / 5 minutes

Partial discharge:

1.73U₀ The discharge amount at this voltage is no more than 10 pC.z

Installation scenario:

Indoor tunnels and cable trenches, etc., cannot withstand mechanical external forces.





MYJV 8.7/10 kV Coal Mine Used XLPE Insulated PVC Sheathed Power Cable

Specifications

MYJV 8.7/10 kV

Nominal cross-section	Conductor diameter	Insulation nominal thickness	Nominal thickness of the sheath	Outer diameter of the cable	Cable weight	Maximum direct current resistance of the conductor at 20°C	25°C cable current carrying capacity	
mm ²	mm	mm	mm	mm	km/kg	Ω/km	in ground(A)	in air(A)
25	6	4.5	2.4	46.4	2361	0.727	125	120
35	7	4.5	2.5	48.8	2772	0.524	155	140
50	8.3	4.5	2.6	51.8	3357	0.387	180	165
70	9.8	4.5	2.7	55.6	4131	0.268	220	210
95	11.5	4.5	2.8	59.3	5036	0.193	265	255
120	12.9	4.5	2.9	62.5	5919	0.153	300	290
150	14.5	4.5	3	66.4	6998	0.124	340	330
185	16	4.5	3.2	70	8189	0.0991	380	375
240	18.3	4.5	3.3	75.1	10043	0.0754	435	435
300	20.5	4.5	3.5	80.1	12013	0.0601	485	495