



## MYJV22 8.7/10 kV Coal Mine Used XLPE Insulated Steel Tape Armored PVC Sheathed Power Cable

### CABLE STRUCTURE:

#### Conductor:

Copper

#### Insulation:

XLPE

#### Shielding layer:

Copper tape shielding

#### Inner sheath:

PVC

#### Aarmor layer:

Steel tape armoring

#### outer sheath:

PVC

### SPECIFICATION RANGE:

#### Wire Core:

25 - 300 mm<sup>2</sup>

### STANDARD:

MT 818.13-2009

### APPLICATION:

Suitable for fixed installation in power distribution networks with rated voltage of 10 kV or less, or in industrial installations.

### CERTIFICATES:

Our series of mining products have undergone strict review by the National Coal Mine Safety Supervision Bureau and have obtained the Coal Mine Safety Mark Certification (MA Certification), providing a reliable guarantee for coal mine safety production.

### TECHNICAL DATA:

Rated voltage:(U<sub>0</sub>/U)

8.7/10 kV

#### Temperature classification:

The cable conductor is permitted to have a maximum long-term operating temperature not exceeding 90°C. During a short circuit (with the maximum duration not exceeding 5 seconds), the maximum temperature of the cable conductor does not exceed 250°C. When laying the cables on the ground, the ambient temperature during the laying process should not be lower than 0°C.

#### Min.Bending Radius:

3 core : 12(D+d)±5%

#### Finished product voltage test:

Wire core: 30.5kV / 5 minutes

#### Partial discharge:

1.73U<sub>0</sub> The discharge amount at this voltage is no more than 10 pC.z

#### Installation scenario:

It can be used in indoor environments, tunnels, cable trenches, or underground direct burial, in damp environments and areas with high groundwater levels. It can withstand certain mechanical external forces and certain tensile forces. Indoor, tunnels, cable trenches, shafts or underground direct burial, etc., can withstand mechanical external forces and certain tensile forces.





**MYJV22 8.7/10 kV Coal Mine Used XLPE Insulated  
Steel Tape Armored PVC Sheathed Power Cable**

**Specifications**

**MYJV22 8.7/10 kV**

Nominal cross-section	Conductor diameter	Insulation nominal thickness	Nominal thickness of the sheath	Outer diameter of the cable	Cable weight	Maximum direct current resistance of the conductor at 20°C	25°C cable current carrying capacity	
mm <sup>2</sup>	mm	mm	mm	mm	km/kg	Ω/km	in ground(A)	in air(A)
25	6	4.5	2.6	52.8	3660	0.727	150	140
35	7	4.5	2.6	55	4109	0.524	175	170
50	8.3	4.5	2.8	58	4771	0.387	210	205
70	9.8	4.5	2.9	62	5671	0.268	255	250
95	11.5	4.5	3	65.7	6672	0.193	305	310
120	12.9	4.5	3.1	68.9	7639	0.153	350	350
150	14.5	4.5	3.2	72.6	8787	0.124	390	400
185	16	4.5	3.4	77.2	10247	0.0991	440	450
240	18.3	4.5	3.5	82.3	13045	0.0754	510	530
300	20.5	4.5	3.8	87.5	15244	0.0601	565	605